



GENMAC Combiflash RG201HO-M5 MOTOSALDATOR 7,1KVA

Product price:

1.706,00 € tax excluded

Product description:

GENMAC Combiflash RG201HO-M5 SINGLE-PHASE MOTOR WELDER 7,1KVA

The Genmac Combiflash RG201HO-M5 singlephase motor welder is equipped with a Honda gasoline engine capable of delivering a power of 7,1KVA with a maximum welding current of 200A.

The small size and moderate weight of the single-phase 7.1KVA Genmac Combiflash RG201HO-M5 motor welder make it one of the most popular professional products in the Genmac line.

Fitted with a Honda GX390 engine capable of delivering a power of 7.1KVA with gasoline supply and an "air" cooling system by means of a fan, it guarantees maximum efficiency and durability even for long and continuous work both as a generator and as a welder. The motorwelder generates a maximum power of 7.1KVA in just 3000 rpm.

These features make the Genmac motorwelder, one of the most appreciated products on the market for its high quality/price ratio.

The start-up of the Genmac Combiflash RG201HO-M5, motorwelder takes place through the classic "pull" system.

His lightness and the possibility of requesting a mobilization kit, is very appreciated by those customers who deal with repairs on streets or squares and that for reasons of lack or remoteness of parking for their car, they must take behind the motor-welder by hand for considerable distances (old town, inconvenient areas etc.)

On the side, the motorwelder is equipped with 1 current output with 230V 16A SCHUKO type attack and 1 of the 230V 32A CEE type suitable for the connection of any electrical appliance of





common use.

TECHNICAL FEATURES OF THE MOTORWELDER GENMAC Combiflash RG201HO-M5 7,1KVA

Power Supply: Gasoline
Start: Manual
Phase Type: SinglePhase
Maximum Power: 7.1KVA / 6.4KW
Welding Current: 60 - 200 A
Maximum Welding Current: 200 A ac
Service (A): 200 - 35% / 180 - 60%
Welding Type: Electrode
Voltage: 230V
Frequency: 50 Hz
3000 rpm
Tank: 19 Lt.
Autonomy @ 75%: 9 h fixed rpm
Length (mm): 810
Width (mm): 550
Height (mm): 680
Dry weight (Kg): 95

If you are looking for another product then you can consult on our catalog other MOTOR WELDER.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 6.4
Maximum power single phase (KVA): 7.1
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Engine: Honda GX390
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Pull starter
Cooling: Air
Poles: 2
Welding current (A): 200 - 35% / 180 - 60%





Type of welding: MMA
Current max (A): 200
Fuel tank capacity (L): 19
Running time (h): 9
Length (mm): 810
Width (mm): 550
Height (mm): 680
Dry weight (Kg): 95
Silenced: Yes
Super silenced: No
Voltage regulator: No
Engine manufacturer: Honda