



# MECC ALTE ECP28-VL/2 C-TYPE THREE-PHASE ALTERNATOR 40KVA

## Product description:

MECC ALTE ECP28-VL/2 C-TYPE ALTERNATOR 40KVA THREEPHASE

Alternator MECC ALTE ECP28-VL/2 C-TYPE with a power of 40KVA, this unit has a Brushless self-exciting and self-regulating operation equipped with voltage regulator **DSR**.

The ECP28-VL/2 C-TYPE alternator is designed to operate at 50 or 60 HZ frequency, the possibility of working on these two frequencies makes it possible to apply it for any service voltage increasing its versatility, for the correct operation it is only necessary to verify that the calibrations are correct for the intended use.

MECC ALTE ECP28-VL/2 C-TYPE is supplied with 12 terminals (7 terminals), with which it is normally possible to connect the alternator both in series star and parallel star. According to the needs it is possible to pass from a connection to another one keeping in mind that it is necessary to verify the DSR connection.

MECC ALTE ECP28-VL/2 is equipped with digital current regulator DSR . The regulator is suitable for operation on both threephase generators, allowing fast, accurate and reliable set-up.

All MECC ALTE ECP28 alternators have the MAUX auxiliary winding to power the DSR digital regulator. You can connect the DSR voltage regulator to your PC via the DxR2 USB interface and DxR TERMINAL software to query/download alarms and settings for analysis. The DSR has a built-in USB connection and can be connected to the PC without any optional connection card.

Select the alternator that reflects the **technical specifications you require**, visit our dedicated section to find out how.

## TECHNICAL FEATURES OF 30KVA MECC ALTE ALTERNATOR ECP28-VL/2 C-TYPE

PhaseType: SinglePhase / ThreePhase  
Threephase maximum Power: 38. 4KW





---

Threephase continuous power: 32KW  
Threephase maximum power: 48KVA  
Threephase continuous power: 40KVA  
Frequency: 50 / 60 Hz  
Voltage: 230 / 400 V  
Protection class: IP23  
Alternator speed: 3000 rpm  
Number of poles: 2  
Efficiency: 87. 9%  
Weight: 156 Kg  
Width: 4667 mm  
Length: 593 mm  
Height: 460 mm  
Constant speed alternator  
Brushless  
Voltage regulator: AVR / DSR

Looking for a product with different features? Here you can find the full range MECC ALTE and other specialized brands.

Images and technical data are not binding and subject to changes by the manufacturer

#### **Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 24 (50Hz) - 29 (60Hz)  
Continuous power single phase (KW): 22.2 (50Hz) - 26.4 (60Hz)  
Maximum power single phase (KVA): 24 (50Hz) - 29 (60Hz)  
Continuous power single phase (KVA): 22.2 (50Hz) - 26.4 (60Hz)  
Maximum power three phase (KW): 32 (50Hz) - 38.4 (60Hz)  
Continuous power three phase (KW): 29.6 (50Hz) - 35.2 (60Hz)  
Maximum power three phase (KVA): 40 (50Hz) - 48 (60Hz)  
Continuous power three phase (KVA): 37 (50Hz) - 44 (60Hz)  
Frequency (Hz): 50 / 60  
Voltage (V): 230 / 400  
Engine rpm (rpm): 3000  
Poles: 2  
Single-phase power (KVA): 29  
Three-phase power (KVA): 48  
Efficiency (%): 88.3  
Protection degree: IP23  
Acoustic pressure: 74 dB(A) at 7 m  
Length (mm): 466





Width (mm): 593  
Height (mm): 460  
Brushes: No  
PMG: No  
Type of alternator: Constant Speed  
Voltage regulator: AVR  
Weight (Kg): 156