



MASE IS 24.6 K MARINE GENERATOR SINGLE- PHASE 24KW EPA

Product description:

MASE IS 24.6 K SINGLE-PHASE MARINE GENERATOR 24KW

MASE IS24,6K single-phase marine generator with KUBOTA V2403 engine with diesel power supply at 1800 rpm capable of delivering a power of 24KW.

The MASE IS24,6K marine generator is designed with a soundproof cabin that makes it **supersilenced**. The MASE IS24,6K is built with Kubota diesel-powered engine and synchronous alternator, self-excited with air/water cooling. With its small size, it is also suitable on small boats.

The marine generator CBU control module has a new design, the latest technology, a large display and micro-buttons for quick navigation of menus, start and stop procedures; IP54 protection rating. Very compact, 86x124mm and equipped with 10mts shielded cable, the CBU module has multiple functions for complete monitoring of the MASE IS24.6K.

The soundproof cabin of the MASE IS24,6K is made of an aluminum profile structure that supports panels in marine aluminum painted type 5754 extremely light and very high resistance to external agents. The excellent accessibility to the internal compartment makes maintenance operations easier, even when the generator set is installed in narrow spaces.

The MASE IS24.6K marine generator has **EPA certification** valid only for the **U.S. market**

Technical Features:

Phase Type: Single Phase

Maximum Power: 24KW

Fuel: Diesel

Voltage: 120 / 240 V

Frequency: 60 Hz

Engine: KUBOTA V2403, 4 Stroke

Length: 1115 mm





Width: 585 mm
Height: 730 mm
Weight: 475 Kg

If you are looking for another generator like the MASE IS24,6K then you can see the entire catalog of marine generator sets.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 24
Fuel: Diesel
Frequency (Hz): 60
Voltage (V): 120 / 240
Engine: KUBOTA V2403
Engine rpm (rpm): 1800
Speed governor: Electronic
Engine capacity (cm³): 2197
Number cylinders: 4
Cooling: Air / water (Intercooler W/A)
Inyección : Indirect
Alternator: Synchronous, self-excited
Poles: 4
Lubrication: Forced
Consumption (L/h): 6.5
Acoustic pressure: 49 dB(A) at 7 m
Length (mm): 1115
Width (mm): 585
Height (mm): 730
Dry weight (Kg): 475
Inverter: No
AVR: Yes
Compound: No
Silenced: Yes
Super silenced: Yes





Shop name



PrestaShop