



ZIPWAKE IT450-S V22 INTERCEPTOR WITH 3 METERS CABLE

Product description:

ZIPWAKE IT450-S V22 INTERCEPTOR WITH 3 METERS CABLE

ZIPWAKE IT450-S V22 are centerline-mounted V-interceptors perfect for filling the space between two outboards or stern drives, even with dual propeller propulsion.

ZIPWAKE IT450-S V22 effectively covers sterndrive angles between 11 and 24 degrees. Centerline mounted interceptors can be included in new installations or retrofitted to existing systems.

When space between multiple outboards or sterndrives is tight, a ZIPWAKE IT450-S V22 interceptor offers a viable alternative for additional pitch and roll control not possible with a without degrading propeller performance.

Because of their special blade shape, ZIPWAKE IT450-S V22 interceptors generate a narrower wake, thereby mitigating propeller inflow disturbance and also allowing installation between outboards mounted at their minimum offset.

The modular design allows boat designers to develop their own innovative applications, such as in multihulls or high-speed boats with stepped hulls.

ZIPWAKE IT450-S V22 TECHNICAL FEATURES

Maximum boat speed: 60 knots
Blade stroke: 30 mm (1.2 in)
Blade speed: 20 mm/s (0.8 in/s)
Cable routing: concealed hull or above the waterline
Servo actuator: SU-S
Cable length: 3 m (10 ft), extendable to 6 m (20 ft)
Cable material: PUR





Connector: M12 5-pin circular
Connector diameter: 14.5 mm (0.57 in)
Power supply voltage: 12 - 32 V DC
Power consumption: 25 W max.
Operating temperature: 0° to +40°C (+32° to +104°F)
Storage temperature: -40° to +90°C (-40° to +194°F)
Protection rating: IP68 5 m (16 ft)
Compliance: CE, FCC
Length: 450 mm
Depth: 56 mm
Height angle: 19°
Max height: 174 mm
Weight: 3.3 Kg

Looking for an interceptor with different features? [HERE](#) you can find the entire range ZIPWAKE or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Protection degree: IP68
Speed (Km/h): 60 knots max.
Input power (W): 25
Power cable length (m): 3
Operating temperature (°C): 0° to +40°C
Length (mm): 56
Width (mm): 450
Height (mm): 174
Product type: Interceptor
Colour: Black
Weight (Kg): 3.3
Video: 7NbCTly_km0

