



MASE SILENT 6000 B/A GENERATOR 3.6 KW SINGLE-PHASE STAGE V AVR

Product price:

3.565,00 € tax excluded

Product description:

MASE SILENT 6000 B/A SINGLE-PHASE GENERATOR 3.6 KW

MASE SILENT 6000 B/A is a single-phase generator equipped with a Honda GX270 OHV gasoline engine, capable of delivering a maximum power of 3.6 KW.

The MASE SILENT 6000 B/A single-phase generator provides reliable power for home, business and recreational environments, safely powering appliances and other electronic devices.

The generator is as easy to install and operate as it is to start and stop with clear, intuitive controls. MASE SILENT 6000 B/A is equipped with a honda GX270 OHV gasoline engine. They are very reliable engines that ensure efficient combustion and **low fuel consumption**, they also feature a protection system that causes the engine to stop if the oil level is too low.

MASE SILENT 6000 B/A are designed for stationary applications and to meet every need, these generators are characterized by reliability and quiet operation. The units include electric start-up and provision for operation with an automatic control unit. The MASE SILENT 6000 B/A are equipped with **10.5lt tank** with a large cap that is convenient to unscrew even with work gloves

MASE SILENT 6000 B/A has an all-steel construction and a large metal tank. The generator guarantees an efficient and silent operation thanks to the Honda GX270 OHV which allows to deliver a maximum power of 3.6 KW.

The generator is supplied with:

- Automatic stop for low oil level
- 12V built-in battery
- 1 single-phase socket CEE 230V - 16A
- Power output protections





- Differential circuit breaker
- Voltmeter
- Hour meter
- Fixed wheels and concealable handles for handling

TECHNICAL FEATURES MASE SILENT 6000 B/A

Maximum power Single-phase: 3.6 KW

Continuous use power Single-phase: 3. 2 KW

Fuel: Gasoline

Voltage: 230 V

Frequency: 50 Hz

Motor: Honda GX270 OHV

Engine speed: 3000 rpm

Displacement: 270 cm³

Cooling: Air

Start: Electric

Fuel tank capacity: 10. 5 l

Consumption: 2.2 Lt/h at 75% load

Acoustic power: 86 dB (61 dB at 7 m)

Protection class: IP 23

Length: 1059 mm

Width: 670 mm

Height: 740 mm

Weight: 138 Kg

Are you looking for a power generator with different characteristics? Here you can find the full range of products from MASE or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Phase: Single phase

Maximum power single phase (KW): 3.6

Continuous power single phase (KW): 3.2

Maximum power single phase (KVA): 3.6

Continuous power single phase (KVA): 3.2

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 2 x 230V 16A CE

Engine: Honda GX270, 4 tempi, OHV, aspirato naturalmente





Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm³): 270

Number cylinders: 1

Oil capacity (L): 1.1

Cooling: Air

Alternator: Sincrono, autoeccitato, autoregolato, senza spazzole

Poles: 2

Fuel tank capacity (L): 10.5

Consumption (L/h): 1.9 at 75% of the load

Running time (h): 5.5 at 75% of the load

Acoustic power: 89 dB(A)

Acoustic pressure: 64 dB(A) at 7 m

Length (mm): 942

Width (mm): 588

Height (mm): 720

Dry weight (Kg): 125

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Honda

