

BINDA POMPA EXCELSIOR - G E00 GB

Product price:

10.191,00 € tax excluded

Product description:

BINDA PUMP EL PTP500

BINDA Pump EL PTP500, the company continues the traditional production of hand pumps, which began in 1919, aiming at a constant technological evolution of the product, satisfying the needs of its customers, respecting the environment and always guaranteeing an excellent quality/price ratio of its articles. It has reached world leadership in the management of fluids by means of manual pumping systems, offering the most complete range of pumps and complementary articles available on the international market. The BINDA PUMP company, RINA certified and an official NATO supplier, guarantees thehigh quality standard of its production, thanks to control systems that have been implemented according to the above-mentioned military standards.

The BINDA PUMP EL PTP500 is the ideal solution for testing the tightness of pipes, tanks and other hydraulic components. It is simple to use and guarantees accurate results.

Technical specifications BINDA PUMP EL PTP500:

Diameter: 3/8"

Pressure (bar): 500ù

Maximum flow rate (Lt/min): 15

Voltage (V): 400 Power (kW): 15 Weight: 132 Kg

BINDA EL PTP500:

BINDA High-pressure hydraulic test pump. Equipped with pressure regulator, 100 litre tank, pressure gauge, coil, shut-off and drain valve and flexible delivery hose.

BINDA EL PTP500 is supplied on standard trolley only





BINDA PUMP EL PTP500: Hydraulic test pump, equipped with regulator and complete with 100 litre tank, pressure gauge, coil and shut-off and drain valve. Dispensing pipe on request. BINDA EL PTP500 supplied on trolley only and with dispensing tube as standard.

The BINDA EL PTP500 is made of high-quality materials and complies with the most stringent international regulations. It is therefore the ideal choice for companies needing a reliable and durable product.

if you are looking for a product similar to BINDA or with similar characteristics click HERE.

Images are purely indicative.

Product features:

Maximum power single phase (KW): 15

Voltage (V): 400

Maximum output capacity (Lt/min): 15

Diameter (Ø): 1"1/2 Pressure (bars): 8 Weight (Kg): 0.4

