



SINCRO E3 2-24/120

Synchronous DC Alternator

2.9 KW AVR

Product description:

Designed for applications requiring 24 & 48 VDC low voltage supply, Sincro DC power solutions are suitable both as battery chargers and emergency power supplies of auxiliary circuits, in the telecommunication, transports and industrial field.

Applications

- Battery chargers
- Low voltage LED light towers
- Power supply of auxiliary circuits, high/medium voltage disconnectors coils, signalling devices
- Power supply of monitoring and alarm systems

General features

- AVR electronic voltage regulation
- Based on three-phase synchronous alternators
- 1500 rpm or 3000 rpm with large speed tolerance
- Constant DC output voltage
- Adjustable output voltage
- Current overload protection
- Fan cooled
- Complying with EN 60034-1, IEC 60034-1, ISO 8528-3

Sectors of use

- Telecommunications
- Industry
- Transports
- Military

Advantages

- High voltage stability in a large speed range
- High efficiency
- Low voltage ripple





- High reliability
- Available with the most common couplings
- Fast recovery time during transient by step load variation

Not binding images and technical data.

Product features:

Frequency (Hz): 50

Voltage (V): 24

Engine rpm (rpm): 3000

Poles: 2

Power (KW): 2.9

Protection degree: IP23

Current (A): 120

Brushes: Yes

Type of alternator: Constant Speed

Voltage regulator: AVR

Weight (Kg): 20.2